



SAFETY DATA SHEET

Stendec Crystal Oil 2.5wt

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Stendec Crystal Oil 2.5wt

Product number 7015

Internal identification GHS21447

1.2. Relevant identified uses of the substance or mixture and uses advised against

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Super Alloy Racing Ltd

Plough Farm House

Greenfield Road,

Holywell

CH8 7PZ

+44 (0) 1352 710999

+44 (0) 7413 134763

info@superalloyracing.com

Manufacturer

STENDEC/ Super Alloy Racing Ltd

Plough Farm House

Greenfield Road,

Holywell

CH8 7PZ

+44 (0) 1352 710999

+44 (0) 7413 134763

info@superalloyracing.com

1.4. Emergency telephone number

Emergency telephone +44(0) 7413 134763

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC/1272/2008)

Physical hazards Not Classified

Health hazards Asp. Tox. 1 - H304

Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC)

-

2.2. Label elements

1/10

Revision date: 24/11/2015 Revision: 1

Stendec Crystal Oil 2.5wt

Pictogram

Signal word Danger

Hazard statements H304 May be fatal if swallowed and enters airways.

Precautionary statements P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501a Dispose of contents/container to hazardous or special waste collection point.

Contains White Mineral Oil, Lubricating Oil (Petroleum) C15-30 hydro treated neutral oil-based,

Lubricating oil (petroleum) C20-C50, hydro treated, neutral oil based

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

White Mineral Oil 60-100%

CAS number: 92062-35-6 EC number: 295-550-3 REACH registration number: 01-

2119487078-27-XXXX

Classification

Asp. Tox. 1 - H304

Classification (67/548/EEC or 1999/45/EC)

Xn;R65.

Lubricating Oil (Petroleum) C15-30 hydro treated neutral oil based 10-30%

CAS number: 72623-86-0 EC number: 276-737-9 REACH registration number: 01-

2119474878-16-XXXX

Classification

Asp. Tox. 1 - H304

Classification (67/548/EEC or 1999/45/EC)

-

Lubricating oil (petroleum) C20-C50,hydrotreated,neutral oil based

1-5%

CAS number: 72623-87-1 EC number: 276-738-4

Classification

Asp. Tox. 1 - H304

Classification (67/548/EEC or 1999/45/EC)

-

Isopropyl oleate 1-5%

CAS number: 112-11-8

Classification

Not Classified

Classification (67/548/EEC or 1999/45/EC)

-

2/10

Revision date: 24/11/2015 Revision: 1

Stendec Crystal Oil 2.5wt

2,6 Di-tert-butylphenol <1%

CAS number: 128-39-2 EC number: 204-884-0

M factor (Acute) = 1 M factor (Chronic) = 1

Classification

Skin Irrit. 2 - H315

Aquatic Acute 1 - H400

Aquatic Chronic 1 - H410

Classification (67/548/EEC or 1999/45/EC)

N;R50/53.

Highly refined mineral oil (C15 - C50) <1%

CAS number: —

Classification

Not Classified

Classification (67/548/EEC or 1999/45/EC)

-

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention if any discomfort continues.

Inhalation If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Get medical attention if any

discomfort continues.

Ingestion Get medical attention if any discomfort continues. Do not induce vomiting. Product contains petroleum based material, which, if aspirated into the lungs may result in chemical pneumonia.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed
General information If aspiration into the lungs is suspected, eg when vomiting, admit to hospital immediately.

Inhalation Upper respiratory irritation.

Ingestion May cause discomfort if swallowed. The product contains mineral oil, which if aspirated into the lungs through vomiting after ingestion, may result in chemical pneumonia. May be fatal if swallowed and enters airways.

Skin contact Prolonged contact may cause redness, irritation and dry skin.

Eye contact Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

3/10

Revision date: 24/11/2015 Revision: 1

Stendec Crystal Oil 2.5wt

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Heat from fire could result in drums bursting

Hazardous combustion

products

Protection against nuisance dust must be used when the airborne concentration exceeds 10

mg/m³. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.

5.3. Advice for firefighters

Protective actions during firefighting

Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions for personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.

6.2. Environmental precautions

Environmental precautions Contain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking

containers. Spillages or uncontrolled discharges into watercourses must be reported

immediately to the Environmental Agency or other appropriate regulatory body. In case of

spillage on water prevent the spread by use of suitable barrier equipment

6.4. Reference to other sections

Reference to other sections for personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Always remove oil with soap and water or skin cleaning agent, never use

organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags

moistened with oil into pockets.

Advice on general occupational hygiene

Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

4/10

Revision date: 24/11/2015 Revision: 1

Stendec Crystal Oil 2.5wt

8.1. Control parameters

Occupational exposure limits

White Mineral Oil

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³ mist

Lubricating Oil (Petroleum) C15-30 hydro treated neutral oil-based

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³

Isopropyl oleate

Long-term exposure limit (8-hour TWA): OES 5 mg/m³

Short-term exposure limit (15-minute): OES 10 mg/m³

Highly refined mineral oil (C15 - C50)

Long-term exposure limit (8-hour TWA): 5 mg/m³

WEL = Workplace Exposure Limit

ACGIH = American Conference of Governmental Industrial Hygienists.

8.2. Exposure controls

Protective equipment

Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. The following protection should be worn:

Chemical splash goggles or face shield.

Hand protection the most suitable glove should be chosen in consultation with the glove

supplier/manufacturer, who can provide information about the breakthrough time of the glove

material.

Other skin and body protection

Use barrier creams to prevent skin contact.

Hygiene measures Use engineering controls to reduce air contamination to permissible exposure level. Wash promptly with soap and water if skin becomes contaminated.

Respiratory protection No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

Thermal hazards Not anticipated under normal conditions of use. The product is combustible if heated excessively and an ignition source is applied.

Environmental exposure controls

Do not allow product to contaminate land.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Straw.

Odour Characteristic. Oil-like.

Odour threshold Not determined.

pH Not applicable.

5/10

Revision date: 24/11/2015 Revision: 1

Stendec Crystal Oil 2.5wt

Melting point -36°C

Initial boiling point and range $>320^{\circ}\text{C}$ @ 101.3 kPa

Flash point 124°C PMCC (Pensky-Martens closed cup).

Upper/lower flammability or explosive limits

Not known.

Other flammability Product is not flammable but on excessive heating may become combustible.

Vapour pressure <0.1 kPa @ 20°C

Vapour density Not determined.

Relative density 0.850 @ 15.6°C

Solubility(ies) Insoluble in water. Soluble in the following materials:
Organic solvents.

Partition coefficient Not determined.

Auto-ignition temperature Not determined.

Decomposition Temperature Not determined.

Viscosity 10.3 cSt @ 40°C

Explosive properties Not considered to be explosive.

Explosive under the influence

of a flame

Not considered to be explosive.

Oxidising properties the mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.

9.2. Other information

Volatile organic compound the product is a complex mixture, the majority of which would not be classed as a VOC.

However, it cannot be discounted that trace or low levels of VOC's may be present.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions

Unlikely to occur under normal conditions of use. Unlikely to occur.

10.4. Conditions to avoid

Conditions to avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products

Oxides of carbon. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³.

SECTION 11: Toxicological information

6/10

Revision date: 24/11/2015 Revision: 1

Stendec Crystal Oil 2.5wt

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Not expected to be highly toxic based on information of ingredients.

Acute toxicity - dermal

Notes (dermal LD₅₀) Not expected to be highly toxic based on information of ingredients.

Serious eye damage/irritation

Serious eye damage/irritation May cause mild, short lasting discomfort to eyes.

Respiratory sensitisation

Respiratory sensitisation No evidence to suggest the product will be a respiratory sensitizer. Repeated exposure to oil mists may cause respiratory damage.

Skin sensitisation

Skin sensitisation Not expected to be a skin sensitizer based on information on components.

Reproductive toxicity

Reproductive toxicity - fertility No data available to suggest the product will cause reproductive toxicity.

Aspiration hazard

Aspiration hazard Kinematic viscosity ≤ 20.5 cSt @ 40 C. Aspiration hazard if swallowed.

Ingestion Swallowing significant quantities may cause discomfort, nausea, diarrhoea and irritation of the digestive tract. Aspiration into the lungs (e.g. through vomiting) after ingestion can be

hazardous with possible resultant chemically induced pneumonia. May be fatal if swallowed and enters airways.

Skin contact Skin irritation should not occur when used as recommended. Repeated exposure may cause skin dryness or cracking.

Eye contact May cause temporary eye irritation.

Acute and chronic health hazards

Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis and skin cancer.

SECTION 12: Ecological Information

Eco toxicity the product is not expected to be hazardous to the environment.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability the product is not classed as being readily biodegradable by OECD test methods but is considered inherently biodegradable.

Stability (hydrolysis) The product is based on highly refined mineral oils that are considered stable to hydrolysis.

Biodegradation The product is not considered readily biodegradable, albeit the major constituents are expected to ultimately biodegrade.

Biological oxygen demand Not determined.

Chemical oxygen demand Not determined.

12.3. Bio accumulative potential

Bio accumulative potential Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

Partition coefficient Not determined.

7/10

Revision date: 24/11/2015 Revision: 1

Stendec Crystal Oil 2.5wt

12.4. Mobility in soil

Mobility The product is non-volatile. The product is insoluble in water and will spread on the water surface.

Henry's law constant Not determined.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste.

Dispose of waste to licensed waste disposal site

in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class European waste catalogue (EWC) number = 13 02 05* (mineral based non-chlorinated engine, gear & lubricating oils)

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to

Annex II of MARPOL 73/78

and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

8/10

Revision date: 24/11/2015 Revision: 1

Stendec Crystal Oil 2.5wt

National regulations Health and Safety at Work etc. Act 1974 (as amended).

The Pollution Prevention and Control Act 1999.

Special Waste regulations 1996.

Control of Pollution (Oil Storage) (England) Regulations 2001

The Chemicals (Hazard Information and Packaging for Supply)

Regulations 2009 (SI 2009

No. 716).

EU legislation Dangerous Preparations Directive 1999/45/EC.

Dangerous Substances Directive 67/548/EEC.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Guidance Workplace Exposure Limits EH40.

Safety Data Sheets for Substances and Preparations.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

All the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines – PICCS

All the ingredients are listed or exempt.

New Zealand - NZIOC

All the ingredients are listed or exempt.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 24/11/2015

Revision 1

SDS number 21447

Risk phrases in full Not classified.

9/10

Revision date: 24/11/2015 Revision: 1

Stendec Crystal Oil 2.5wt

Hazard statements in full H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

10/10