



Product Information:

STENDEC EASY GLIDE GREASE

Description:

STENDEC EASY GLIDE GREASE is a premium quality, water resistant grease for use in industrial and marine applications where the presence of water and humid atmospheres can affect lubricating performance and be detrimental to the protection of parts from corrosion. K99 is suitable for plain and antifriction bearings.

Features:

- High degree of water resistance.
- Excellent corrosion protection.
- Good sealing properties.

Applications:

Recommended for all plain and rolling element bearings operating in very wet conditions. STENDEC EASY GLIDE GREASE is an ideal choice if bearings are temporarily immersed in water or if there is contact with corrosive products. This product may be used in stern tubes where a grease of this consistency and type is recommended.

As with all greases used for the first time, check compatibility with the grease applied previously and if necessary purge prior to application. Likewise, as a general rule, take care not to over-lubricate and apply the quantity of grease recommended by the manufacturer.

Performance Level:

DIN 51502 K2/3G-20

ISO 6743-9 L-XBCHB2/3

Physical Characteristics:

Appearance Amber

NLGI Consistency 2/3

Thickener Calcium 12 hydroxystearate

Base Oil Solvent refined mineral oil

Base Oil Viscosity @ 40 oC (cSt) 110

Worked Penetration 240 to 260

Dropping Point (oC) 140 min

Oil Separation (%) 3

Copper Corrosion Pass

Water Washout @ 38 oC (%) 2

Operating Temperature Range (oC) -20 to 110